


DECLARATION OF PERFORMANCE

according to Regulation (EU) 305/2011
N.DoP: 1036 - CRM - 11/09/2025

1. Unique identification code of the product-type:	NEOSEN PLUS					EN
	P948836 (Invicta) - 7090050600I (CM)					
Models:						
2. Intended uses:	Residencial space heating appliance fired by wood without hot water supply					
3. Name, registered trade name or registered trade mark and contact address of the manufacturer:	INVICTA Zone Industrielle lieu-dit « la gravette » 08350 DONCHERY – FRANCE - Tél: +33 0324 277171					
5. System or systems of assessment and verification of constancy of performance of the construction product:						System 3
6. Notified body:	0476 - Kiwa Cermet Italia S.p.A.					
Test report number:	2013895					
7. Harmonised technical specification:	EN 16510-1:2022 / EN 16510-2-1:2022					
8. Essential characteristics:						
Mechanical resistance and stability						
Maximum load of a chimney the appliance max carry				mchim	0	kg
Safety in case of fire - Protection of combustible materials						
Minimum distance to combustible materials - bottom				dB	0	mm
Minimum distance to combustible materials - front floor				dF	1500	mm
Minimum distance to combustible materials - ceiling				dC	750	mm
Minimum distance to combustible materials - rear				dR	600	mm
Minimum distance to combustible materials - side				dS	800	mm
Minimum distance to combustible materials - lateral radiation				dL	1500	mm
Minimum distance to combustible materials - frontal radiation				dP	1500	mm
Thickness of protective insulating material				s	0	mm
Hygiene, health and the environment - Emission of combustion products						
				nom		part
Carbon Monoxide emission (CO at 13% O ₂)				CO	1500	mg/Nm ³
Nitrogen Oxides emission (NO _x at 13% O ₂)				NO _x	200	mg/Nm ³
Emission of Organic Gaseous Compounds (OGC at 13% O ₂)				OCG	80	mg/Nm ³
Particulate Matter emission (PM at 13% O ₂)				PM	40	mg/Nm ³
Safety and accessibility in use - Data for installation to a chimney						
				nom		part
Flue gas outlet temperature				Ts	277	°C
Minimum flue draught				p	10	Pa
Flue gas mass flow				Φf,g	7,4	g/s
Fire safety of installation to the chimney - Flue temperature class				Tclass	T400G	
Energy economy and heat retention - Heat output, efficiency and space heating efficiency						
				nom		part
Heat output				P	8,0	kW
Space heat output				PSH	8,0	kW
Water heat output, if applicable				PW	0,0	kW
Efficiency				η	81,0	%
Seasonal space heating efficiency at nominal heat output				ηs	71	%
Energy efficiency index				EEI	107	-
Energy efficiency class				Class	-	
Consumption of electrical auxiliary energy at nominal heat output				elmax	0,000	kW
Consumption of electrical auxiliary energy at part load heat output				elmin	0,000	kW
Consumption of electrical auxiliary energy at standby				elSB	0,000	kW
Sustainable use of natural resources						
Environmental sustainability				NDP		
9. The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.						
Signed for and on behalf of the manufacturer by					Signature	
Contact Person	Function	Date	Place			
ing. Andrea Tezza	Technical Manager	11/09/2025	Vivier-au-Court			