


# DECLARATION OF PERFORMANCE

according to Regulation (EU) 305/2011  
N.DoP: 1021 - CRM - 27/06/2025

|                                                                                                                                                                                                                                                                             |                                                                                                                              |                 |                 |                                                                                       |                        |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|-----------------|-----------------|---------------------------------------------------------------------------------------|------------------------|
| 1. Unique identification code of the product-type:                                                                                                                                                                                                                          | <b>NOLA STYLE ETANCHE 8 Wi-Fi</b> <span style="float: right;">EN</span>                                                      |                 |                 |                                                                                       |                        |
|                                                                                                                                                                                                                                                                             | P64468x (Invicta) - 72410554xxI (CM)                                                                                         |                 |                 |                                                                                       |                        |
| Models:                                                                                                                                                                                                                                                                     |                                                                                                                              |                 |                 |                                                                                       |                        |
| 2. Intended uses:                                                                                                                                                                                                                                                           | Residencial space heating appliance fired by wood pellets without hot water supply                                           |                 |                 |                                                                                       |                        |
| 3. Name, registered trade name or registered trade mark and contact address of the manufacturer:                                                                                                                                                                            | <b>INVICTA</b><br><b>Zone Industrielle lieu-dit « la gravette »</b><br><b>08350 DONCHERY – FRANCE - Tél: +33 0324 277171</b> |                 |                 |                                                                                       |                        |
| 5. System or systems of assessment and verification of constancy of performance of the construction product:                                                                                                                                                                |                                                                                                                              |                 |                 |                                                                                       | System 3 and 4         |
| 6. Notified body:                                                                                                                                                                                                                                                           | 0051 - IMQ S.p.A.                                                                                                            |                 |                 |                                                                                       |                        |
| Test report number:                                                                                                                                                                                                                                                         | CS25-0120229-01                                                                                                              |                 |                 |                                                                                       |                        |
| 7. Harmonised technical specification:                                                                                                                                                                                                                                      | EN 16510-1:2022 / EN 16510-2-6:2022                                                                                          |                 |                 |                                                                                       |                        |
| 8. Essential characteristics:                                                                                                                                                                                                                                               |                                                                                                                              |                 |                 |                                                                                       |                        |
| <b>Mechanical resistance and stability</b>                                                                                                                                                                                                                                  |                                                                                                                              |                 |                 |                                                                                       |                        |
| Maximum load of a chimney the appliance max carry                                                                                                                                                                                                                           |                                                                                                                              | mchim           | 20              | kg                                                                                    |                        |
| <b>Safety in case of fire - Protection of combustible materials</b>                                                                                                                                                                                                         |                                                                                                                              |                 |                 |                                                                                       |                        |
| Minimum distance to combustible materials - bottom                                                                                                                                                                                                                          |                                                                                                                              | dB              | 0               | mm                                                                                    |                        |
| Minimum distance to combustible materials - front floor                                                                                                                                                                                                                     |                                                                                                                              | dF              | 1000            | mm                                                                                    |                        |
| Minimum distance to combustible materials - ceiling                                                                                                                                                                                                                         |                                                                                                                              | dC              | 750             | mm                                                                                    |                        |
| Minimum distance to combustible materials - rear                                                                                                                                                                                                                            |                                                                                                                              | dR              | 100             | mm                                                                                    |                        |
| Minimum distance to combustible materials - side                                                                                                                                                                                                                            |                                                                                                                              | dS              | 200             | mm                                                                                    |                        |
| Minimum distance to combustible materials - lateral radiation                                                                                                                                                                                                               |                                                                                                                              | dL              | 750             | mm                                                                                    |                        |
| Minimum distance to combustible materials - frontal radiation                                                                                                                                                                                                               |                                                                                                                              | dP              | 2000            | mm                                                                                    |                        |
| Thickness of protective insulating material                                                                                                                                                                                                                                 |                                                                                                                              | s               | 0               | mm                                                                                    |                        |
| <b>Hygiene, health and the environment - Emission of combustion products</b>                                                                                                                                                                                                |                                                                                                                              |                 |                 |                                                                                       |                        |
|                                                                                                                                                                                                                                                                             |                                                                                                                              | <b>nom</b>      |                 | <b>part</b>                                                                           |                        |
| Carbon Monoxide emission (CO at 13% O <sub>2</sub> )                                                                                                                                                                                                                        |                                                                                                                              | CO              | 300             | mg/Nm <sup>3</sup>                                                                    | 300 mg/Nm <sup>3</sup> |
| Nitrogen Oxides emission (NO <sub>x</sub> at 13% O <sub>2</sub> )                                                                                                                                                                                                           |                                                                                                                              | NO <sub>x</sub> | 200             | mg/Nm <sup>3</sup>                                                                    | 200 mg/Nm <sup>3</sup> |
| Emission of Organic Gaseous Compounds (OGC at 13% O <sub>2</sub> )                                                                                                                                                                                                          |                                                                                                                              | OCG             | 5               | mg/Nm <sup>3</sup>                                                                    | 60 mg/Nm <sup>3</sup>  |
| Particulate Matter emission (PM at 13% O <sub>2</sub> )                                                                                                                                                                                                                     |                                                                                                                              | PM              | 20              | mg/Nm <sup>3</sup>                                                                    | 20 mg/Nm <sup>3</sup>  |
| <b>Safety and accessibility in use - Data for installation to a chimney</b>                                                                                                                                                                                                 |                                                                                                                              |                 |                 |                                                                                       |                        |
|                                                                                                                                                                                                                                                                             |                                                                                                                              | <b>nom</b>      |                 | <b>part</b>                                                                           |                        |
| Flue gas outlet temperature                                                                                                                                                                                                                                                 |                                                                                                                              | Ts              | 193             | °C                                                                                    | 96 °C                  |
| Minimum flue draught                                                                                                                                                                                                                                                        |                                                                                                                              | p               | 7               | Pa                                                                                    | 5 Pa                   |
| Flue gas mass flow                                                                                                                                                                                                                                                          |                                                                                                                              | Φf,g            | 5,5             | g/s                                                                                   | 3,0 g/s                |
| Fire safety of installation to the chimney - Flue temperature class                                                                                                                                                                                                         |                                                                                                                              | Tclass          | T200G           |                                                                                       |                        |
| <b>Energy economy and heat retention - Heat output, efficiency and space heating efficiency</b>                                                                                                                                                                             |                                                                                                                              |                 |                 |                                                                                       |                        |
|                                                                                                                                                                                                                                                                             |                                                                                                                              | <b>nom</b>      |                 | <b>part</b>                                                                           |                        |
| Heat output                                                                                                                                                                                                                                                                 |                                                                                                                              | P               | 8,0             | kW                                                                                    | 3,1 kW                 |
| Space heat output                                                                                                                                                                                                                                                           |                                                                                                                              | PSH             | 8,0             | kW                                                                                    | 3,1 kW                 |
| Water heat output, if applicable                                                                                                                                                                                                                                            |                                                                                                                              | PW              | 0,0             | kW                                                                                    | 0,0 kW                 |
| Efficiency                                                                                                                                                                                                                                                                  |                                                                                                                              | η               | 90,0            | %                                                                                     | 94,0 %                 |
| Seasonal space heating efficiency at nominal heat output                                                                                                                                                                                                                    |                                                                                                                              | ηs              | 86              | %                                                                                     |                        |
| Energy efficiency index                                                                                                                                                                                                                                                     |                                                                                                                              | EEI             | 126             | -                                                                                     |                        |
| Energy efficiency class                                                                                                                                                                                                                                                     |                                                                                                                              | Class           | A+              | -                                                                                     |                        |
| Consumption of electrical auxiliary energy at nominal heat output                                                                                                                                                                                                           |                                                                                                                              | elmax           | 0,063           | kW                                                                                    |                        |
| Consumption of electrical auxiliary energy at part load heat output                                                                                                                                                                                                         |                                                                                                                              | elmin           | 0,043           | kW                                                                                    |                        |
| Consumption of electrical auxiliary energy at standby                                                                                                                                                                                                                       |                                                                                                                              | elSB            | 0,004           | kW                                                                                    |                        |
| <b>Sustainable use of natural resources</b>                                                                                                                                                                                                                                 |                                                                                                                              |                 |                 |                                                                                       |                        |
| Environmental sustainability                                                                                                                                                                                                                                                |                                                                                                                              | NDP             |                 |                                                                                       |                        |
| 9. The performance of the product identified above is in conformity with the set of declared performance.<br>This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. |                                                                                                                              |                 |                 |                                                                                       |                        |
| Signed for and on behalf of the manufacturer by                                                                                                                                                                                                                             |                                                                                                                              |                 |                 |                                                                                       | Signature              |
| Contact Person                                                                                                                                                                                                                                                              | Function                                                                                                                     | Date            | Place           |  |                        |
| ing. Andrea Tezza                                                                                                                                                                                                                                                           | Technical Manager                                                                                                            | 27/06/2025      | Vivier-au-Court |                                                                                       |                        |